

STOCK # **95**

CRUSHED STONE /
MODERATE SERVICE



* **DIN RATING**

120

ABRASION LOSS!

SUPERIOR ARMORING!
STATIC CONDUCTIVE!

PRC GRD II / PACIFIC

COMPOUND / SBR - (STYRENE BUTADIENE RUBBER)

TENSILE (PSI)	ELONGATION (%)	MODULUS (300%)	TEMP. RATING	DURO (HARDNESS)	SPEC. GRAVITY
2400	640	1100	-40 / 220°F.	60 ± 5	1.14

CARCASS / POLYESTER – NYLON – (PLAIN WEAVE or STRAIGHT & FILL)

<i>PRC</i>	*8:1 Safety	2 / 220	3 / 330	4 / 440
Fabric Type		P/P	P/P	P/P
Vulcanized & Fastener Rating (piw)		220	330	440
Carcass Gauge (in.)		.086	.129	.152
Carcass Weight (lbs/sq.ft.)		.59	.88	1.04
Approx 1/32 cover wt (lbs/sq.ft.)		.18	.18	.18
Avg. Permanent Elongation (%)		1.5%	1.5%	1.5%
Elastic modulus (piw)		16,000	24,000	32,000
Recommended Fastener Plate		140	190	BR-10
Hinge		R2	R5	R5

TROUGHABILITY (Minimum Belt Width) (in.)

<i>PRC</i>	2 / 220	3 / 330	4 / 440
20 degree idlers	14	14	20
35 degree idlers	14	20	26
45 degree idlers	16	26	32

MINIMUM PULLEY DIAMETERS (in.)

<i>PRC</i>	2 / 220	3 / 330	4 / 440
Over 80% Tension	14	16	17
60% to 80% Tension	12	14	15

LOAD SUPPORT (Maximum Belt Width) (in.)

<i>PRC</i>	2 / 220	3 / 330	4 / 440
0 - 40 lbs/cu.ft.	36	54	54
41 - 80 lbs/cu.ft.	30	42	48
81 -120 lbs/cu.ft.	30	42	42
Over 120 lbs/cu.ft.	—	36	36

Price Rubber fully warrants & guarantees all products against material defect & workmanship for the life of the product. Price Belts are manufactured to width so they run true from the start and Price uses 100% polyester textiles to keep stretch to a minimum! Each & every Price Belt is engineered, custom built, & available in either smooth or textured finishes for job-matched performance. Experience the Price Advantage . . . Value that Lasts!



Price RUBBER CORP.



FOR MORE INFORMATION, CONTACT YOUR LOCAL PRICE RUBBER DISTRIBUTOR OR CALL **PRC** CUSTOMER SERVICE:

WATTS: (800) 633-1470 • FAX: (334) 271-3194

www.pricerubber.com