



## P-14 WATER DISCHARGE

**COMPOUND / SBR - (STYRENE BUTADIENE RUBBER)** 

TENSILE	ELONGATION	MODULUS	TEMP.	DURO	SPEC.
(PSI)	(%)	( 300% )	RATING	(HARDNESS)	GRAVITY
2400	640	1100	-40 / 180°	60 ± 5	1.14

## CARCASS / 100% POLYESTER - ( PLAIN WEAVE, WARP & FILL) CONSTRUCTION: HAND BUILT, MANDREL WRAPPED.





COLOR / SERVICE: Black-Ideal for Construction Sites Requiring

Higher Working Pressures. High Abrasion Weather

Resistance.

TUBE: SBR of 1/8", 1/4", 3/8" Thicknesses.

**REINFORCEMENT**: Multiple Plies of 110 lb. Polyester Fabric.

COVER: SBR 1/16" Thick.

PACKAGING: 10' Min. / 30' Max. with Plain Ends:

**Branding**: No Brand.

ID	Ply	WP	
4"	4	150	
5"	4	150	
6"	4	125	
8"	4	100	
10"	5	100	
12"	6	100	



Made in U.S.A!

Price Rubber fully warrants and guarantees all products against material defect and workmanship for the life of the product. PRC Hoses are custom built and precision made. Price uses 100% polyester textiles to give maximum protection against "burst" and will not rot, mildew, or wick moisture! Each & every PRC Hose is custom engineered with a nylon wrapped textured finish for job-matched performance. Experience the Price Advantage . . .

> Value that Lasts! 🦰 RUBBER CORP.