

STOCK # 22

GRADE II X-TRA
WATER SUCTION



S-75 ROUGH NECK

COMPOUND / SBR - (STYRENE BUTADIENE RUBBER)

TENSILE (PSI)	ELONGATION (%)	MODULUS (300%)	TEMP. RATING	DURO (HARDNESS)	SPEC. GRAVITY
2400	640	1100	-40 / 220°	60 ± 5	1.14

CARCASS / 100% POLYESTER – (PLAIN WEAVE, WARP & FILL)

CONSTRUCTION: HAND BUILT, MANDREL WRAPPED.

S-75

COLOR / SERVICE: Black-High Abrasion Weather Resistance.

TUBE: SBR of 1/8", 1/4", 3/8" Thicknesses.

REINFORCEMENT: Multiple Plies of 110 lb. Polyester Fabric with a Galvanized Steel Spring Wire.

COVER: SBR 1/16" Thick.

PACKAGING: 10' Min. / 30' Max. with Plain Ends:

BRANDING: No Brand.



PRC ID	Ply	OD	WP	Bending Radius	Wt / Ft	Wire OAG
4"	2	4.8"	60	36"	2.6	.110
5"	2	5.8"	50	48"	3.2	.110
6"	2	6.8"	40	60"	3.8	.110
8"	3	9.1"	30	72"	6.7	.148
10"	4	11.3"	25	84"	10.1	.148
12"	5	13.5"	20	96"	13.8	.148

Price Rubber fully warrants and guarantees all products against material defect and workmanship for the life of the product. PRC Hoses are custom built and precision made. Price uses 100% polyester textiles to give maximum protection against "burst" and will not rot, mildew, or wick moisture! Each & every PRC Hose is custom engineered with a nylon wrapped textured finish for job-matched performance. Experience the Price Advantage . . .

Value that Lasts!

Price RUBBER CORP.

FOR MORE INFORMATION, CONTACT YOUR LOCAL PRICE RUBBER DISTRIBUTOR OR CALL PRC CUSTOMER SERVICE:

WATTS: (800) 633-1470 • FAX: (334) 271-3194

www.pricerubber.com